



SGMNQ69430

30V, Power, Single N-Channel, TDFN Package, MOSFET

FEATURES

- Low On-State Resistance
- Low Total Gate Charge and Capacitance Losses
- Small Footprint for Compact Design
- RoHS Compliant and Halogen Free

PRODUCT SUMMARY

$R_{DS(on)}$ (TYP) $V_{GS} = 10V$	$R_{DS(on)}$ (MAX) $V_{GS} = 10V$	I_D (MAX) $T_A = +25^\circ C$
6.3m Ω	7.8m Ω	13A

ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	VALUE	UNITS
Drain-to-Source Voltage		V _{DS}	30	V
Gate-to-Source Voltage		V _{GS}	±20	V
Drain Current ⁽¹⁾	T _A = +25°C	I _D	13	A
	T _A = +70°C		10	
	T _C = +25°C		30	
	T _C = +100°C		20	
Drain Current (Pulse) ⁽²⁾		I _{DM}	60	A
Total Dissipation	T _A = +25°C	P _D	1.9	W
	T _A = +70°C		1.2	
	T _C = +25°C		14	
	T _C = +100°C		5.9	
Avalanche Current ⁽³⁾		I _{AS}	26.5	A
Avalanche Energy ⁽³⁾		E _{AS}	35.1	mJ
Junction Temperature		T _J	+150	°C
Storage Temperature Range		T _{STG}	-55 to +150	°C
Lead Temperature (Soldering, 10s)			+260	°C


Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

NOTES:

1. The current will be limited by Package, PCB, thermal design and operating temperature.
2. $t_{PLUSE} < 10\mu s$.
3. Parts are 100% tested at $V_{GS} = 10V$, $I_L = 19A$, and $E_{AS} = 18.05mJ$.


PIN CONFIGURATION

(TOP VIEW)



TDFN-2x2-6BL

EQUIVALENT CIRCUIT



APPLICATIONS

CPU Power Delivery
DC/DC Converters
Battery Management

PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGMNQ69430	TDFN-2×2-6BL	-55°C to +150°C	SGMNQ69430TTEN6G/TR	1NP XXXX	Tape and Reel, 3000

MARKING INFORMATION

NOTE: XXXX = Date Code, Trace Code and Vendor Code.

YYY— Serial Number
XXXX
└── Vendor Code
└── Trace Code
└── Date Code - Year

Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

THERMAL RESISTANCE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNITS
Junction-to-Case Thermal Resistance	$R_{\theta JC}$	5	°C/W
Junction-to-Ambient Thermal Resistance ⁽¹⁾	$R_{\theta JA}$	65	°C/W







NOTE: 1. $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, 2oz copper on FR4 board.

ELECTRICAL CHARACTERISTICS







(T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Static OFF Characteristics							
Drain-to-Source Breakdown Voltage	V _{BR_DSS}	V _{GS} = 0V, I _D = 250μA		30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{GS} = 0V, V _{DS} = 24V				1	μA
Gate-to-Source Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V				±100	nA
Static ON Characteristics							
Gate-to-Source Threshold Voltage	V _{GS_TH}	V _{GS} = V _{DS} , I _D = 250μA		1.2	1.6	2.2	V
Drain-to-Source On-State Resistance	R _{DSON}	I _D = 10A	V _{GS} = 10V		6.3	7.8	mΩ
			V _{GS} = 4.5V		10.6	13.8	
Forward Transconductance	g _{FS}	V _{DS} = 1.5V, I _D = 10A			20		S
Gate Resistance	R _G	V _{GS} = 0V, V _{DS} = 0V, f = 1MHz			1.3		Ω
Diode Characteristics							
Diode Forward Voltage	V _{F_SD}	V _{GS} = 0V, I _S = 1A			0.8	1.1	V
Reverse Recovery Time	t _{RR}	V _{GS} = 0V, I _S = 10A, di/dt = 100A/μs			19		ns
Reverse Recovery Charge	Q _{RR}				9		nC
Dynamic Characteristics							
Input Capacitance	C _{ISS}	V _{GS} = 0V, V _{DS} = 15V, f = 1MHz			590		pF
Output Capacitance	C _{OSS}				500		
Reverse Transfer Capacitance	C _{RSS}				35		
Total Gate Charge	Q _G	V _{DS} = 15V, I _D = 10A	V _{GS} = 10V		12.4		nC
			V _{GS} = 4.5V		6.3		
Gate-to-Source Charge	Q _{GS}	V _{GS} = 4.5V, V _{DS} = 15V, I _D = 10A			2.3		
Gate-to-Drain Charge	Q _{GD}				3.2		
Switch Characteristics							
Turn-On Delay Time	t _{D_ON}	V _{GS} = 10V, V _{DS} = 15V, I _D = 10A, R _G = 3Ω			3		ns
Rise Time	t _R				29		
Turn-Off Delay Time	t _{D_OFF}				11		
Fall Time	t _F				6		


TYPICAL PERFORMANCE CHARACTERISTICS



TYPICAL PERFORMANCE CHARACTERISTICS (continued)



TYPICAL PERFORMANCE CHARACTERISTICS (continued)



REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


Changes from Original (MAY 2025) to REV.A

Page

Changed from product preview to production data.....All

PACKAGE OUTLINE DIMENSIONS

TDFN-2×2-6BL




NOTE: This drawing is subject to change without notice.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TDFN-2x2-6BL	7"	9.5	2.30	2.30	1.00	4.0	4.0	2.0	8.0	Q1

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

DD0002