

GENERAL DESCRIPTION

The 74LVC541A is an octal buffer/line driver with 3-state outputs. $\overline{OE}1$ and $\overline{OE}2$ are two output enable inputs. When $\overline{OE}1$ and $\overline{OE}2$ are low, data transmits from A_n inputs to the Y_n outputs. When $\overline{OE}1$ or $\overline{OE}2$ is high, all outputs are in high-impedance state. Both 3.3V and 5V devices can drive inputs, enabling this device to operate as translator in a mixed 3.3V and 5V system environment. All inputs support Schmitt-trigger action, allowing slower input rise and fall time.

This device is highly suitable for partial power-down applications using power-off leakage current (I_{OFF}) circuit. When the device is powered down, the current backflow will be prevented from passing through the device.

FUNCTION TABLE

INPUT			OUTPUT
$\overline{OE}1$	$\overline{OE}2$	A_n	Y_n
L	L	L	L
L	L	H	H
X	H	X	Z
H	X	X	Z

H = High Voltage Level

L = Low Voltage Level


Z = High-Impedance State

X = Don't Care

FEATURES

- Supply Voltage Range: 1.2V to 3.6V
- Over-Voltage Tolerant Inputs up to 5.5 V
- CMOS Low Power Dissipation
- +24mA/-24mA Output Current
- Support Partial Power-down Mode
- -40°C to +125°C Operating Temperature Range
- Available in a Green TSSOP-20 Package

LOGIC DIAGRAM




PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
74LVC541A	TSSOP-20	-40°C to +125°C	74LVC541AXTS20G/TR	04QXTS20 XXXXX	Tape and Reel, 4000

MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

XXXXX



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

Supply Voltage, V_{CC}	-0.5V to 6.5V
Input Voltage, V_I ⁽²⁾	-0.5V to 6.5V
Output Voltage, V_O ⁽²⁾	
High-State or Low-State.....	-0.5V to MIN (6.5V, $V_{CC} + 0.5V$)
3-State or Power-down Mode	-0.5V to 6.5V
Input Clamping Current, I_{IK} ($V_I < 0V$).....	-50mA
Output Clamping Current, I_{OK} ($V_O > V_{CC}$ or $V_O < 0V$)...±	50mA
Output Current, I_O	
High-State.....	-50mA
Low-State.....	50mA
Supply Current, I_{CC}	100mA
Ground Current, I_{GND}	-100mA
Junction Temperature ⁽³⁾	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s).....	+260°C
ESD Susceptibility	
HBM.....	6000V
CDM.....	1000V

RECOMMENDED OPERATING CONDITIONS

Function Supply Voltage, V_{CC}	1.2V (MIN)
Operating Supply Voltage, V_{CC}	1.65V to 3.6V
Input Voltage, V_I	0V to 5.5V
Output Voltage, V_O	
High-State or Low-State.....	0V to V_{CC}
3-State or Power-down Mode	0V to 5.5V
Input Transition Rise and Fall Rate, $\Delta t/\Delta V$	
$V_{CC} = 2.3V$ to 2.7V	20ns/V (MAX)
$V_{CC} = 2.7V$ to 3.6V	10ns/V (MAX)
Operating Temperature Range	-40°C to +125°C

OVERSTRESS CAUTION

1. Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.
2. The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.
3. The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.


ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATION



PIN DESCRIPTION

PIN	NAME	FUNCTION
1, 19	$\overline{OE}1$, $\overline{OE}2$	Output Enable Inputs (Active Low).
2, 3, 4, 5, 6, 7, 8, 9	A0, A1, A2, A3, A4, A5, A6, A7	Data Inputs.
18, 17, 16, 15, 14, 13, 12, 11	Y0, Y1, Y2, Y3, Y4, Y5, Y6, Y7	Data Outputs.
10	GND	Ground.
20	V_{CC}	Supply Voltage.

ELECTRICAL CHARACTERISTICS(Full = -40°C to +125°C, all typical values are measured at $V_{CC} = 3.3V$ and $T_A = +25^\circ C$, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS
High-Level Input Voltage	V_{IH}	$V_{CC} = 1.2V$	Full	1.08			V
		$V_{CC} = 1.65V$ to $1.95V$	Full	$0.65 \times V_{CC}$			
		$V_{CC} = 2.3V$ to $2.7V$	Full	1.7			
		$V_{CC} = 2.7V$ to $3.6V$	Full	2			
Low-Level Input Voltage	V_{IL}	$V_{CC} = 1.2V$	Full			0.12	V
		$V_{CC} = 1.65V$ to $1.95V$	Full			$0.35 \times V_{CC}$	
		$V_{CC} = 2.3V$ to $2.7V$	Full			0.7	
		$V_{CC} = 2.7V$ to $3.6V$	Full			0.8	
High-Level Output Voltage	V_{OH}	$V_I = V_{IH}$	$I_O = -100\mu A$, $V_{CC} = 1.65V$ to $3.6V$	Full	$V_{CC} - 0.1$		V
			$I_O = -4mA$, $V_{CC} = 1.65V$	Full	1.35	1.54	
			$I_O = -8mA$, $V_{CC} = 2.3V$	Full	2.0	2.18	
			$I_O = -12mA$, $V_{CC} = 2.7V$	Full	2.35	2.55	
			$I_O = -18mA$, $V_{CC} = 3.0V$	Full	2.5	2.8	
			$I_O = -24mA$, $V_{CC} = 3.0V$	Full	2.3	2.7	
Low-Level Output Voltage	V_{OL}	$V_I = V_{IL}$	$I_O = 100\mu A$, $V_{CC} = 1.65V$ to $3.6V$	Full		0.1	V
			$I_O = 4mA$, $V_{CC} = 1.65V$	Full		0.07	
			$I_O = 8mA$, $V_{CC} = 2.3V$	Full		0.11	
			$I_O = 12mA$, $V_{CC} = 2.7V$	Full		0.16	
			$I_O = 18mA$, $V_{CC} = 3.0V$	Full		0.23	
			$I_O = 24mA$, $V_{CC} = 3.0V$	Full		0.3	
Input Leakage Current	I_I	$V_I = 5.5V$ or GND, $V_{CC} = 3.6V$	Full		± 0.01	± 2	μA
Off-State Output Current	I_{OZ}	$V_I = V_{IH}$ or V_{IL} , $V_O = 5.5V$ or GND, $V_{CC} = 3.6V$	Full		± 0.01	± 10	μA
Power-Off Leakage Current	I_{OFF}	V_I or $V_O = 5.5V$, $V_{CC} = 0V$	Full		0.01	5	μA
Supply Current	I_{CC}	$V_I = V_{CC}$ or GND, $I_O = 0A$, $V_{CC} = 3.6V$	Full		0.05	20	μA
Additional Supply Current	ΔI_{CC}	Per input pin, $V_I = V_{CC} - 0.6V$, $I_O = 0A$, $V_{CC} = 2.7V$ to $3.6V$	Full		0.1	80	μA
Input Capacitance	C_I		+25°C		5		pF

DYNAMIC CHARACTERISTICS

(See Figure 1 for test circuit. Full = -40°C to +125°C, all typical values are measured at T_A = +25°C and V_{CC} = 1.2V, 1.8V, 2.5V, 2.7V and 3.3V respectively, unless otherwise noted.)


PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	UNITS
Propagation Delay ⁽²⁾	t _{PD}	An to Yn, see Figure 2	V _{CC} = 1.2V	+25°C	14		ns
			V _{CC} = 1.65V to 1.95V	Full	0.5	4	
			V _{CC} = 2.3V to 2.7V	Full	0.5	3	
			V _{CC} = 2.7V	Full	0.5	3.5	
			V _{CC} = 3.0V to 3.6V	Full	0.5	3	
Enable Time ⁽²⁾	t _{EN}	$\overline{\text{OEn}}$ to Yn, see Figure 3	V _{CC} = 1.2V	+25°C	20		ns
			V _{CC} = 1.65V to 1.95V	Full	0.5	7	
			V _{CC} = 2.3V to 2.7V	Full	0.5	5	
			V _{CC} = 2.7V	Full	0.5	6	
			V _{CC} = 3.0V to 3.6V	Full	0.5	5.5	
Disable Time ⁽²⁾	t _{DIS}	$\overline{\text{OEn}}$ to Yn, see Figure 3	V _{CC} = 1.2V	+25°C	11		ns
			V _{CC} = 1.65V to 1.95V	Full	0.5	4.5	
			V _{CC} = 2.3V to 2.7V	Full	0.5	3.5	
			V _{CC} = 2.7V	Full	1	4	
			V _{CC} = 3.0V to 3.6V	Full	1	4	
Power Dissipation Capacitance ⁽³⁾	C _{PD}	Per input, V _I = GND to V _{CC}	V _{CC} = 1.65V to 1.95V	+25°C	12		pF
			V _{CC} = 2.3V to 2.7V	+25°C	13		
			V _{CC} = 3.0V to 3.6V	+25°C	14		

NOTES:

- Specified by design and characterization, not production tested.
- t_{PD} is the same as t_{PLH} and t_{PHL}. t_{EN} is the same as t_{PZL} and t_{PZH}. t_{DIS} is the same as t_{PLZ} and t_{PHZ}.
- C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$$
 where:
 f_i = Input frequency in MHz.
 f_o = Output frequency in MHz.
 C_L = Output load capacitance in pF.
 V_{CC} = Supply voltage in Volts.
 N = Number of inputs switching.
 $\Sigma(C_L \times V_{CC}^2 \times f_o)$ = Sum of the outputs.

TEST CIRCUIT



Test conditions are given in Table 1.

Definitions for test circuit:

R_L : Load resistance.

C_L : Load capacitance (includes jig and probe).

R_T : Termination resistance (equals to output impedance Z_O of the pulse generator).


V_{EXT} : External voltage used to measure switching time.

Figure 1. Test Circuit for Measuring Switching Times

Table 1. Test Conditions

SUPPLY VOLTAGE	INPUT		LOAD		V_{EXT}		
V_{CC}	V_I	t_R, t_F	C_L	R_L	t_{PLH}, t_{PHL}	t_{PLZ}, t_{PZL}	t_{PHZ}, t_{PZH}
1.2V	V_{CC}	$\leq 2.0\text{ns}$	30pF	1k Ω	Open	$2 \times V_{CC}$	GND
1.65V to 1.95V	V_{CC}	$\leq 2.0\text{ns}$	30pF	1k Ω	Open	$2 \times V_{CC}$	GND
2.3V to 2.7V	V_{CC}	$\leq 2.0\text{ns}$	30pF	500 Ω	Open	$2 \times V_{CC}$	GND
2.7V	2.7V	$\leq 2.5\text{ns}$	50pF	500 Ω	Open	$2 \times V_{CC}$	GND
3.0V to 3.6V	2.7V	$\leq 2.5\text{ns}$	50pF	500 Ω	Open	$2 \times V_{CC}$	GND

WAVEFORMS




Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 2. Input (An) to Output (Yn) Propagation Delays



Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 3. Enable and Disable Times

Table 2. Measurement Points

SUPPLY VOLTAGE	INPUT		OUTPUT		
V_{CC}	V_I	$V_M^{(1)}$	V_M	V_X	V_Y
1.2V	V_{CC}	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
1.65V to 1.95V	V_{CC}	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
2.3V to 2.7V	V_{CC}	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
2.7V	2.7V	1.5V	1.5V	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$
3.0V to 3.6V	2.7V	1.5V	1.5V	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$

NOTE: 1. The measurement points should be V_{IH} or V_{IL} when the input rising or falling time exceeds 2.5ns.



REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


Changes from Original (DECEMBER 2022) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

TSSOP-20



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	6.400	-	6.600
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		


NOTES:

1. Body dimensions do not include mold flash or protrusion.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-153.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TSSOP-20	13"	16.4	6.80	6.90	1.50	4.0	8.0	2.0	16.0	Q1

DD00001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002