



GENERAL DESCRIPTION

The SGM8051/3 (single), SGM8052/5 (dual) and SGM8054 (quad) are low cost, high speed, voltage feedback amplifiers. These devices can operate from 2.5V to 5.5V single supply, and consume 2.3mA low quiescent current per amplifier. And, the supply current of SGM8053/5 is only 75 μ A per amplifier in power-down mode. So SGM8053/5 are suitable for battery-powered equipment and portable devices, which require low power dissipation. The SGM8051/2/3/4/5 provide a wide input common mode voltage range and rail-to-rail output voltage swing.

These devices are designed to provide optimal performance in all aspects. They exhibit a wide bandwidth of 250MHz ($G = +1$) and a 0.1dB gain flatness of 37MHz ($G=+2$). The short settling time and low distortion make the operational amplifiers appropriate for buffering high speed ADC and DAC.

The SGM8051 is available in Green SOT-23-5 and SOIC-8 packages. The SGM8052 is available in Green SOIC-8 and MSOP-8 packages. The SGM8053 is available in Green SOT-23-6 and SOIC-8 packages. The SGM8054 is available in Green SOIC-14 and TSSOP-14 packages. The SGM8055 is available in a Green MSOP-10 package. They are specified over the extended -40°C to +125°C temperature range.


APPLICATIONS

Professional Video
Photodiode Preamplifier
ADC
Filter
Imaging
Hand Set
DVD
Base Station

SGM8051/SGM8052/SGM8053 SGM8054/SGM8055 250MHz, Rail-to-Rail Output, CMOS Operational Amplifiers

FEATURES

- Low Cost
- High Speed:
 - 3dB Bandwidth ($G = +1$): 250MHz
 - Slew Rate: 130V/ μ s
 - Settling Time to 0.1% with 2V Step: 58ns
- Excellent Video Performance ($R_L = 150\Omega$, $G = +2$):
 - 0.1dB Gain Flatness: 37MHz
 - Diff Gain Error: 0.03%
 - Diff Phase Error: 0.08°
- Input Offset Voltage: 8mV (MAX)
- Input Voltage Range: -0.2V to 3.8V with $V_S = 5V$
- Rail-to-Rail Output
- Supply Voltage Range: 2.5V to 5.5V
- Low Supply Current:
 - 2.3mA/Amplifier (TYP)
 - 75 μ A/Amplifier Shutdown Current for SGM8053/5
- -40°C to +125°C Operating Temperature Range
- Small Packaging:
 - SGM8051 Available in Green SOT-23-5 and SOIC-8 Packages
 - SGM8052 Available in Green MSOP-8 and SOIC-8 Packages
 - SGM8053 Available in Green SOT-23-6 and SOIC-8 Packages
 - SGM8054 Available in Green TSSOP-14 and SOIC-14 Packages
 - SGM8055 Available in a Green MSOP-10 Package




PACKAGE/ORDERING INFORMATION

MODEL	CHANNEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM8051	Single	SOT-23-5	-40°C to +125°C	SGM8051XN5/TR	8051	Tape and Reel, 3000
		SOIC-8	-40°C to +125°C	SGM8051XS/TR	SGM8051XS XXXXX	Tape and Reel, 2500
SGM8052	Dual	MSOP-8	-40°C to +125°C	SGM8052XMS/TR	SGM8052 XMS XXXXX	Tape and Reel, 3000
		SOIC-8	-40°C to +125°C	SGM8052XS/TR	SGM8052XS XXXXX	Tape and Reel, 2500
SGM8053	Single with Shutdown	SOT-23-6	-40°C to +125°C	SGM8053XN6/TR	SOFXX	Tape and Reel, 3000
		SOIC-8	-40°C to +125°C	SGM8053XS/TR	SGM8053XS XXXXX	Tape and Reel, 2500
SGM8054	Quad	SOIC-14	-40°C to +125°C	SGM8054XS14/TR	SGM8054XS14 XXXXX	Tape and Reel, 2500
		TSSOP-14	-40°C to +125°C	SGM8054XTS14/TR	SGM8054 XTS14 XXXXX	Tape and Reel, 3000
SGM8055	Dual with Shutdown	MSOP-10	-40°C to +125°C	SGM8055XMS/TR	SGM8055 XMS XXXXX	Tape and Reel, 3000


MARKING INFORMATION

NOTE: XX = Date Code. XXXXX = Date Code and Vendor Code.

SOT-23-6



SOIC-8/MSOP-8/SOIC-14/TSSOP-14/MSOP-10



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS

Supply Voltage, $+V_S$ to $-V_S$	6V
Input Common Mode Voltage Range	($-V_S$) - 0.1V to ($+V_S$) + 0.1V
Signal Input Terminals Voltage Range	($-V_S$) - 0.3V to ($+V_S$) + 0.3V
Package Thermal Resistance @ $T_A = +25^\circ C$	
SOT-23-5, θ_{JA}	190°C/W
SOT-23-6, θ_{JA}	190°C/W
SOIC-8, θ_{JA}	125°C/W
MSOP-8, θ_{JA}	216°C/W
MSOP-10, θ_{JA}	216°C/W
Junction Temperature	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s)	+260°C
ESD Susceptibility	
HBM	1000V
MM	400V

RECOMMENDED OPERATING CONDITIONS

Operating Temperature Range

-40°C to +125°C

OVERSTRESS CAUTION

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.







ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATIONS



SGM8051/SGM8052/SGM8053 SGM8054/SGM8055

250MHz, Rail-to-Rail Output, CMOS Operational Amplifiers







ELECTRICAL CHARACTERISTICS

($V_S = 5V$, $G = +2$, $R_F = 887\Omega$, $R_L = 150\Omega$, unless otherwise noted.)

PARAMETER	CONDITIONS	SGM8051/2/3/4/5							
		TYP	MIN/MAX OVER TEMPERATURE						UNITS
		+25°C	+25°C	0°C to +70°C	-40°C to +85°C	-40°C to +125°C			
Dynamic Performance									
-3dB Small-Signal Bandwidth	$G = +1$, $V_{OUT} = 0.1V_{P,P}$, $R_F = 24\Omega$, $R_L = 150\Omega$ $G = +1$, $V_{OUT} = 0.1V_{P,P}$, $R_F = 24\Omega$, $R_L = 1k\Omega$ $G = +2$, $V_{OUT} = 0.1V_{P,P}$, $R_L = 50\Omega$ $G = +2$, $V_{OUT} = 0.1V_{P,P}$, $R_L = 150\Omega$ $G = +2$, $V_{OUT} = 0.1V_{P,P}$, $R_L = 1k\Omega$ $G = +2$, $V_{OUT} = 0.1V_{P,P}$, $R_L = 10k\Omega$ $G = +10$, $R_L = 150\Omega$ $G = +10$, $R_L = 1k\Omega$	180 250 40 80 130 160 90 120						MHz	TYP
Gain-Bandwidth Product	$G = +2$, $V_{OUT} = 0.1V_{P,P}$, $R_L = 150\Omega$, $R_F = 887\Omega$	37						MHz	TYP
Bandwidth for 0.1dB Flatness	$G = +1$, 2V output step	93/-118						V/μs	TYP
Slew Rate	$G = +2$, 2V output step	116/-103						V/μs	TYP
Rise-and-Fall Time	$G = +2$, 4V output step	130/-130						V/μs	TYP
Settling Time to 0.1%	$G = +2$, $V_{OUT} = 0.2V_{P,P}$, 10% to 90%	4						ns	TYP
Overload Recovery Time	$G = +2$, $V_{OUT} = 2V_{P,P}$, 10% to 90%	14						ns	TYP
	$G = +2$, 2V output step	58						ns	TYP
	$V_{IN} \cdot G = +V_S$	18						ns	TYP
Noise/Distortion Performance									
Input Voltage Noise Density	$f = 1MHz$	8.1						nV/√Hz	TYP
Differential Gain Error (NTSC)	$G = +2$, $R_L = 150\Omega$	0.03						%	TYP
Differential Phase Error (NTSC)	$G = +2$, $R_L = 150\Omega$	0.08						degree	TYP
DC Performance									
Input Offset Voltage (V_{OS})		±2						mV	MAX
Input Offset Voltage Drift		4.4						μV/°C	TYP
Input Bias Current (I_B)		6						pA	TYP
Input Offset Current (I_{OS})		2						pA	TYP
Open-Loop Gain (A_{OL})	$V_{OUT} = 0.3V$ to $4.7V$, $R_L = 150\Omega$ $V_{OUT} = 0.2V$ to $4.8V$, $R_L = 1k\Omega$	80 104	75 92	74 91	74 91	73 80		dB	MIN
Input Characteristics									
Input Common Mode Voltage Range (V_{CM})		-0.2 to 3.8						V	TYP
Common Mode Rejection Ratio (CMRR)	$V_{CM} = -0.1V$ to $3.5V$	80	66	65	65	62		dB	MIN
Output Characteristics									
Output Voltage Swing from Rail	$R_L = 150\Omega$	0.12						V	TYP
	$R_L = 1k\Omega$	0.03						V	TYP
Output Current		130	100	95	90	84		mA	MIN
Closed-Loop Output Impedance	$f < 100kHz$	0.08						Ω	TYP
Power-Down (SGM8053/5 Only)									
Turn-On Time		236						ns	TYP
Turn-Off Time		52						ns	TYP
<u>DISABLE</u> Voltage-Off		0.8						V	MAX
<u>DISABLE</u> Voltage-On		2						V	MIN
Output Leakage Current (I_{OFF}) (SGM8055 Only)	$\text{DISABLE} = 0V$, $V_S = 5V$, $V_{OUT} = 5V$	50						pA	TYP
Power Supply									
Operating Voltage Range		2.5 5.5	2.7 5.5	2.7 5.5	2.7 5.5	2.7 5.5		V	MIN
Quiescent Current/Amplifier		2.3 75	3.2 120	3.4 127	3.8 130	4 137		mA	MAX
Supply Current/Amplifier when Disabled (SGM8053/5 only)		75	120	127	130	137		μA	MAX
Power Supply Rejection Ratio (PSRR)	$V_S = 2.7V$ to $5.5V$, $V_{CM} = (-V_S) + 0.5V$	80	67	67	65	62		dB	MIN







TYPICAL PERFORMANCE CHARACTERISTICS

At $T_A = +25^\circ\text{C}$, $V_S = 5\text{V}$, $G = +2$, $R_F = 887\Omega$, $R_G = 887\Omega$ and $R_L = 150\Omega$ connected to $V_S/2$, unless otherwise noted.









TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_S = 5\text{V}$, $G = +2$, $R_F = 887\Omega$, $R_G = 887\Omega$ and $R_L = 150\Omega$ connected to $V_S/2$, unless otherwise noted.









TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_S = 5\text{V}$, $G = +2$, $R_F = 887\Omega$, $R_G = 887\Omega$ and $R_L = 150\Omega$ connected to $V_S/2$, unless otherwise noted.





TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_S = 5\text{V}$, $G = +2$, $R_F = 887\Omega$, $R_G = 887\Omega$ and $R_L = 150\Omega$ connected to $V_S/2$, unless otherwise noted.



TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_S = 5\text{V}$, $G = +2$, $R_F = 887\Omega$, $R_G = 887\Omega$ and $R_L = 150\Omega$ connected to $V_S/2$, unless otherwise noted.



APPLICATION INFORMATION

Rail-to-Rail Output

The SGM8051/2/3/4/5 support rail-to-rail output operation. In single power supply application, for example, when $+V_S = 5V$, $-V_S = GND$, $1k\Omega$ load resistor is tied from OUT pin to ground, the typical output swing range is from 0.03V to 4.97V.

Driving Capacitive Loads

The SGM8051/2/3/4/5 are not designed for driving heavy capacitive load. If greater capacitive load must be driven in application, the circuit in Figure 1 can be used. In this circuit, the IR drop voltage generated by R_{ISO} is compensated by feedback loop.




Figure 1. Circuit to Drive Heavy Capacitive Load

Power Supply Decoupling and Layout

A clean and low noise power supply is very important in amplifier circuit design, besides of input signal noise, the power supply is one of important source of noise to the amplifiers through $+V_S$ and $-V_S$ pins. Power supply bypassing is an effective method to clear up the noise at power supply, and the low impedance path to ground of decoupling capacitor will bypass the noise to GND. In application, $10\mu F$ ceramic capacitor paralleled with $0.1\mu F$ or $0.01\mu F$ ceramic capacitor is used in Figure 2. The ceramic capacitors should be placed as close as possible to $+V_S$ and $-V_S$ power supply pins.




Figure 2. Amplifier Power Supply Bypassing

Grounding

In low speed application, one node grounding technique is the simplest and most effective method to eliminate the noise generated by grounding. In high speed application, the general method to eliminate noise is to use a complete ground plane technique, and the whole ground plane will help distribute heat and reduce EMI noise pickup.

Reduce Input-to-Output Coupling

To reduce the input-to-output coupling, the input traces must be placed as far away from the power supply or output traces as possible. The sensitive trace must not be placed in parallel with the noisy trace in same layer. They must be placed perpendicularly in different layers to reduce the crosstalk. These PCB layout techniques will help to reduce unwanted positive feedback and noise.

APPLICATION INFORMATION (continued)

Typical Application Circuits

Difference Amplifier

The circuit in Figure 3 is a design example of classical difference amplifier. If $R_4/R_3 = R_2/R_1$, then $V_{OUT} = (V_P - V_N) \times R_2/R_1 + V_{REF}$.




Figure 3. Difference Amplifier

Active Low-Pass Filter

The circuit in Figure 4 is a design example of active low-pass filter, the DC gain is equal to $-R_2/R_1$ and the -3dB corner frequency is equal to $1/2\pi R_2 C$. In this design, the filter bandwidth must be less than the bandwidth of the amplifier, the resistor values must be selected as low as possible to reduce ringing or oscillation generated by the parasitic parameters in PCB layout.




Figure 4. Active Low-Pass Filter

Driving Video

The SGM8051/2/3/4/5 can be used in video applications as shown in Figure 5.




Figure 5. Typical Video Driving

REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

JUNE 2017 – REV.E to REV.E.1	Page
Changed Package/Ordering Information section.....	2
Changed Absolute Maximum Ratings section.....	3
Updated Electrical Characteristics section	5



MAY 2014 – REV.D.4 to REV.E	Page
Changed Package/Ordering Information section.....	2

JANUARY 2013 – REV.D.3 to REV.D.4	Page
Updated Package Outline Dimensions section	12 ~ 18
Added Tape and Reel Information section	19, 20



PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

SOT-23-5



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950 BSC		0.037 BSC	
e1	1.900 BSC		0.075 BSC	
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°


NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.


PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

SOT-23-6



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950 BSC		0.037 BSC	
e1	1.900 BSC		0.075 BSC	
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°


NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.

PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

SOIC-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.27 BSC		0.050 BSC	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°


NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.



PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

MSOP-8



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.820	1.100	0.032	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.250	0.380	0.010	0.015
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
E	2.900	3.100	0.114	0.122
E1	4.750	5.050	0.187	0.199
e	0.650 BSC		0.026 BSC	
L	0.400	0.800	0.016	0.031
θ	0°	6°	0°	6°



NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.



PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

MSOP-10



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.820	1.100	0.032	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.180	0.280	0.007	0.011
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
E	2.900	3.100	0.114	0.122
E1	4.750	5.050	0.187	0.199
e	0.500 BSC		0.020 BSC	
L	0.400	0.800	0.016	0.031
θ	0°	6°	0°	6°



NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.



PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

SOIC-14



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
A2	1.25	1.65	0.049	0.065
A3	0.55	0.75	0.022	0.030
b	0.36	0.49	0.014	0.019
D	8.53	8.73	0.336	0.344
E	5.80	6.20	0.228	0.244
E1	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
L	0.45	0.80	0.018	0.032
L1	1.04 REF		0.040 REF	
L2	0.25 BSC		0.01 BSC	
R	0.07		0.003	
R1	0.07		0.003	
h	0.30	0.50	0.012	0.020
θ	0°	8°	0°	8°



NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.



PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

TSSOP-14



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A		1.200		0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	4.860	5.100	0.191	0.201
E	4.300	4.500	0.169	0.177
E1	6.250	6.550	0.246	0.258
e	0.650 BSC		0.026 BSC	
L	0.500	0.700	0.02	0.028
H	0.25 TYP		0.01 TYP	
θ	1°	7°	1°	7°


NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SOT-23-5	7"	9.5	3.20	3.20	1.40	4.0	4.0	2.0	8.0	Q3
SOT-23-6	7"	9.5	3.23	3.17	1.37	4.0	4.0	2.0	8.0	Q3
SOIC-8	13"	12.4	6.40	5.40	2.10	4.0	8.0	2.0	12.0	Q1
MSOP-8	13"	12.4	5.20	3.30	1.50	4.0	8.0	2.0	12.0	Q1
MSOP-10	13"	12.4	5.20	3.30	1.20	4.0	8.0	2.0	12.0	Q1
SOIC-14	13"	16.4	6.60	9.30	2.10	4.0	8.0	2.0	16.0	Q1
TSSOP-14	13"	12.4	6.80	5.40	1.50	4.0	8.0	2.0	12.0	Q1

100000

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18
13"	386	280	370	5

DD0002