



SGM8603

1.1mA, 11MHz, Low Noise, Rail-to-Rail I/O Tiny Package, CMOS Operational Amplifier

GENERAL DESCRIPTION

The SGM8603 (single with shutdown) is a low voltage, low noise and low power operational amplifier, which can operate from 2.1V to 5.5V single supply, while consuming only 1.1mA quiescent current at 5V. The supply current is less than 1 μ A in power-down mode.

The SGM8603 features a 4.9mV maximum input offset voltage. The minimum input common mode voltage is within 0.1V below the negative rail, and the output swing is rail-to-rail with heavy loads. It exhibits a high gain-bandwidth product of 11MHz and a slew rate of 8.5V/ μ s. These specifications make the operational amplifier appropriate for various applications.

The SGM8603 is available in a Green TDFN-2x2-6L package. It is specified over the extended -40°C to +125°C industrial temperature range.

FEATURES

- Input Offset Voltage: 1.1mV (TYP)
- High Gain-Bandwidth Product: 11MHz
- High Slew Rate: 8.5V/ μ s
- Settling Time to 0.1% with 2V Step: 0.21 μ s
- Overload Recovery Time: 0.6 μ s
- Low Noise: 8.5nV/ $\sqrt{\text{Hz}}$ at 10kHz
- Rail-to-Rail Input and Output
- Supply Voltage Range: 2.1V to 5.5V
- Input Voltage Range: -0.1V to 5.6V with V_S = 5.5V
- Low Power:
 - 1.1mA (TYP) Supply Current
 - Less than 1 μ A when Disabled
- -40°C to +125°C Operating Temperature Range
- Available in a Green TDFN-2x2-6L Package

APPLICATIONS


Sensors
Audio
Active Filters
A/D Converters
Communications
Test Equipment
Cellular and Cordless Phones
Laptops and PDAs
Photodiode Amplification
Battery-Powered Instrumentation

PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM8603	TDFN-2x2-6L	-40°C to +125°C	SGM8603XTDI6G/TR	8603 XXXX	Tape and Reel, 3000

MARKING INFORMATION

NOTE: XXXX = Date Code.

XXXX

Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS

Supply Voltage, $+V_S$ to $-V_S$	6V
Input Common Mode Voltage Range	($-V_S$) - 0.3V to ($+V_S$) + 0.3
Junction Temperature	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s)	+260°C
ESD Susceptibility	
HBM	4000V
MM	400V
CDM	1000V

RECOMMENDED OPERATING CONDITIONS

Input Voltage Range	2.1V to 5.5V
Operating Temperature Range	-40°C to +125°C

OVERSTRESS CAUTION

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.

ESD SENSITIVITY CAUTION


This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATION

(TOP VIEW)



TDFN-2x2-6L

NOTE 1: Exposed pad can be connected to $-V_S$ or left floating.

SGM8603

1.1mA, 11MHz, Low Noise, Rail-to-Rail I/O Tiny Package, CMOS Operational Amplifier

ELECTRICAL CHARACTERISTICS

(At $T_A = +25^\circ\text{C}$, $V_S = +5\text{V}$, $V_{CM} = V_S/2$, $R_L = 600\Omega$, unless otherwise noted.)

PARAMETER	CONDITIONS	SGM8603					
		TYP		MIN/MAX OVER TEMPERATURE			
		+25°C	+25°C	-40°C to +85°C	-40°C to +125°C	UNITS	MIN/ MAX
Input Characteristics							
Input Offset Voltage (V_{OS})		1.1	4.9	5.1	5.4	mV	MAX
Input Bias Current (I_B)		1				pA	TYP
Input Offset Current (I_{OS})		1				pA	TYP
Input Common Mode Voltage Range (V_{CM})	$V_S = 5.5\text{V}$	-0.1 to +5.6				V	TYP
Common Mode Rejection Ratio (CMRR)	$V_S = 5.5\text{V}$, $V_{CM} = -0.1\text{V}$ to 4V	83	67	66	65	dB	MIN
	$V_S = 5.5\text{V}$, $V_{CM} = -0.1\text{V}$ to 5.6V	77	61	60	56	dB	MIN
Open-Loop Voltage Gain (A_{OL})	$R_L = 600\Omega$, $V_{OUT} = 0.15\text{V}$ to 4.85V	91	85	73	62	dB	MIN
	$R_L = 10\text{k}\Omega$, $V_{OUT} = 0.05\text{V}$ to 4.95V	105	97	84	69	dB	MIN
Input Offset Voltage Drift ($\Delta V_{OS}/\Delta T$)		2.7				$\mu\text{V}/^\circ\text{C}$	TYP
Output Characteristics							
Output Voltage Swing from Rail	$R_L = 600\Omega$	78	102	123	144	mV	MAX
	$R_L = 10\text{k}\Omega$	7	12	14	20	mV	MAX
Output Current (I_{OUT})		64	52	25	19	mA	MIN
Closed-Loop Output Impedance	$f = 1\text{MHz}$, $G = 1$	8.5				Ω	TYP
Power-Down Disable							
Turn-On Time		1.1				μs	TYP
Turn-Off Time		0.3				μs	TYP
DISABLE Voltage-Off			0.8			V	MAX
DISABLE Voltage-On			2			V	MIN
Power Supply							
Operating Voltage Range			2.1	2.1	2.1	V	MIN
			5.5	5.5	5.5	V	MAX
Power Supply Rejection Ratio (PSRR)	$V_S = 2.1\text{V}$ to 5.5V , $V_{CM} = (-V_S) + 0.5\text{V}$	80	68	67	64	dB	MIN
Quiescent Current (I_Q)	$I_{OUT} = 0$	1.1	1.4	1.6	1.75	mA	MAX
Supply Current when Disabled		0.5	8	9	10	μA	MAX
Dynamic Performance							
Gain-Bandwidth Product (GBP)	$R_L = 10\text{k}\Omega$	11				MHz	TYP
Phase Margin (ϕ_0)		62				$^\circ$	TYP
Full Power Bandwidth (BW_P)	< 1% distortion	400				kHz	TYP
Slew Rate (SR)	$G = 1$, 2V output step	8.5				$\text{V}/\mu\text{s}$	TYP
Settling Time to 0.1% (t_S)	$G = 1$, 2V output step	0.21				μs	TYP
Overload Recovery Time	$V_{IN} \times G = V_S$	0.6				μs	TYP
Noise Performance							
Input Voltage Noise Density (e_n)	$f = 1\text{kHz}$	12.5				$\text{nV}/\sqrt{\text{Hz}}$	TYP
	$f = 10\text{kHz}$	8.5				$\text{nV}/\sqrt{\text{Hz}}$	TYP

SGM8603







**1.1mA, 11MHz, Low Noise, Rail-to-Rail I/O
Tiny Package, CMOS Operational Amplifier**

ELECTRICAL CHARACTERISTICS (continued)







(At $T_A = +25^\circ\text{C}$, $V_S = +2.1\text{V}$, $V_{CM} = V_S/2$, $R_L = 600\Omega$, unless otherwise noted.)

PARAMETER	CONDITIONS	SGM8603					
		TYP		MIN/MAX OVER TEMPERATURE			
		+25°C	+25°C	-40°C to +85°C	-40°C to +125°C	UNITS	MIN/MAX
Input Characteristics							
Input Offset Voltage (V_{OS})		1	5.2	5.5	5.6	mV	MAX
Input Bias Current (I_B)		1				pA	TYP
Input Offset Current (I_{OS})		1				pA	TYP
Input Common Mode Voltage Range (V_{CM})	$V_S = 2.1\text{V}$	-0.1 to +2.2				V	TYP
Common Mode Rejection Ratio (CMRR)	$V_S = 2.1\text{V}$, $V_{CM} = -0.1\text{V}$ to 0.6V	77	60	59	51	dB	MIN
	$V_S = 2.1\text{V}$, $V_{CM} = -0.1\text{V}$ to 2.2V	70	55	53	49	dB	MIN
Open-Loop Voltage Gain (A_{OL})	$R_L = 600\Omega$, $V_{OUT} = 0.15\text{V}$ to 1.95V	88	78	68	58	dB	MIN
	$R_L = 10\text{k}\Omega$, $V_{OUT} = 0.05\text{V}$ to 2.05V	100	89	82	67	dB	MIN
Input Offset Voltage Drift ($\Delta V_{OS}/\Delta T$)		2.9				$\mu\text{V}/^\circ\text{C}$	TYP
Output Characteristics							
Output Voltage Swing from Rail	$R_L = 600\Omega$	38	50	59	66	mV	MAX
	$R_L = 10\text{k}\Omega$	4	9	11	12	mV	MAX
Output Current (I_{OUT})		28	23	17	14	mA	MIN
Closed-Loop Output Impedance	$f = 1\text{MHz}$, $G = 1$	9.3				Ω	TYP
Power-Down Disable							
Turn-On Time		7.7				μs	TYP
Turn-Off Time		0.5				μs	TYP
DISABLE Voltage-Off			0.4			V	MAX
DISABLE Voltage-On			1.8			V	MIN
Power Supply							
Quiescent Current (I_Q)	$I_{OUT} = 0$	1.1	1.4	1.6	1.75	mA	MAX
Supply Current when Disabled		0.5	8	9	10	μA	MAX
Dynamic Performance							
Gain-Bandwidth Product (GBP)	$R_L = 10\text{k}\Omega$	11.5				MHz	TYP
Phase Margin (ϕ_0)		59				°	TYP
Full Power Bandwidth (BW_P)	< 1% distortion	400				kHz	TYP
Slew Rate (SR)	$G = 1$, 2V output step	8				V/ μs	TYP
Settling Time to 0.1% (t_S)	$G = 1$, 2V output step	0.23				μs	TYP
Overload Recovery Time	$V_{IN} \times G = V_S$	1				μs	TYP
Noise Performance							
Input Voltage Noise Density (e_n)	$f = 1\text{kHz}$	15				$\text{nV}/\sqrt{\text{Hz}}$	TYP
	$f = 10\text{kHz}$	9				$\text{nV}/\sqrt{\text{Hz}}$	TYP







TYPICAL PERFORMANCE CHARACTERISTICS

At $T_A = +25^\circ\text{C}$, $V_{CM} = V_S/2$, $R_L = 600\Omega$, unless otherwise noted.







TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{CM} = V_S/2$, $R_L = 600\Omega$, unless otherwise noted.

TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{CM} = V_S/2$, $R_L = 600\Omega$, unless otherwise noted.

TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, $V_{CM} = V_S/2$, $R_L = 600\Omega$, unless otherwise noted.

APPLICATION INFORMATION

Rail-to-Rail Input

When SGM8603 works at the power supply between 2.1V and 5.5V, the input common mode voltage range is from $(-V_S) - 0.1V$ to $(+V_S) + 0.1V$. In Figure 1, the ESD diodes between the inputs and the power supply rails will clamp the input voltage not to exceed the rails.




Figure 1. Input Equivalent Circuit

Rail-to-Rail Output

The SGM8603 supports rail-to-rail output operation. In single power supply application, for example, when $+V_S = 5V$, $-V_S = GND$, 600Ω load resistor is tied from OUT pin to ground, the typical output swing range is from 0.078V to 4.922V.

Driving Capacitive Loads

The SGM8603 is designed for unity-gain stable for capacitive load up to 4700pF. If greater capacitive load must be driven in application, the circuit in Figure 2 can be used. In this circuit, the IR drop voltage generated by R_{ISO} is compensated by feedback loop.




Figure 2. Circuit to Drive Heavy Capacitive Load

Power Supply Decoupling and Layout

A clean and low noise power supply is very important in amplifier circuit design, besides of input signal noise, the power supply is one of important source of noise to the amplifier through $+V_S$ and $-V_S$ pins. Power supply bypassing is an effective method to clear up the noise at power supply, and the low impedance path to ground of decoupling capacitor will bypass the noise to GND. In application, $10\mu F$ ceramic capacitor paralleled with $0.1\mu F$ or $0.01\mu F$ ceramic capacitor is used in Figure 3. The ceramic capacitors should be placed as close as possible to $+V_S$ and $-V_S$ power supply pins.




Figure 3. Amplifier Power Supply Bypassing

Grounding


In low speed application, one node grounding technique is the simplest and most effective method to eliminate the noise generated by grounding. In high speed application, the general method to eliminate noise is to use a complete ground plane technique, and the whole ground plane will help distribute heat and reduce EMI noise pickup.

Reduce Input-to-Output Coupling


To reduce the input-to-output coupling, the input traces must be placed as far away from the power supply or output traces as possible. The sensitive trace must not be placed in parallel with the noisy trace in same layer. They must be placed perpendicularly in different layers to reduce the crosstalk. These PCB layout techniques will help to reduce unwanted positive feedback and noise.

APPLICATION INFORMATION (continued)**Typical Application Circuits****Difference Amplifier**


The circuit in Figure 4 is a design example of classical difference amplifier. If $R_4/R_3 = R_2/R_1$, then $V_{OUT} = (V_P - V_N) \times R_2/R_1 + V_{REF}$.

**Figure 4. Difference Amplifier****High Input Impedance Difference Amplifier**

The circuit in Figure 5 is a design example of high input impedance difference amplifier, the added amplifiers at the input are used to increase the input impedance and eliminate drawback of low input impedance in Figure 4.

**Figure 5. High Input Impedance Difference Amplifier****Active Low-Pass Filter**

The circuit in Figure 6 is a design example of active low-pass filter, the DC gain is equal to $-R_2/R_1$ and the -3dB corner frequency is equal to $1/2\pi R_2 C$. In this design, the filter bandwidth must be less than the bandwidth of the amplifier, the resistor values must be selected as low as possible to reduce ringing or oscillation generated by the parasitic parameters in PCB layout.

**Figure 6. Active Low-Pass Filter**

REVISION HISTORY


NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Original (SEPTEMBER 2015) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

TDFN-2x2-6L



DETAIL A

Pin #1 ID and Tie Bar Mark Options


NOTE: The configuration of the Pin #1 identifier is optional, but must be located within the zone indicated.

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.700	0.800	0.028	0.031
A1	0.000	0.050	0.000	0.002
A2	0.203 REF		0.008 REF	
D	1.900	2.100	0.075	0.083
D1	1.100	1.450	0.043	0.057
E	1.900	2.100	0.075	0.083
E1	0.600	0.850	0.024	0.034
k	0.200 MIN		0.008 MIN	
b	0.180	0.300	0.007	0.012
e	0.650 TYP		0.026 TYP	
L	0.250	0.450	0.010	0.018


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS




NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TDFN-2x2-6L	7"	9.5	2.30	2.30	1.10	4.0	4.0	2.0	8.0	Q1

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

D0002