



# SGM8270N-4

## Low Noise, Precision, High Voltage, Rail-to-Rail I/O Operational Amplifier

### GENERAL DESCRIPTION

The SGM8270N-4 is a quad, low noise, precision operational amplifier, optimized for high voltage operation from 3.3V to 36V single supply or  $\pm 1.65V$  to  $\pm 18V$  dual power supplies. It provides rail-to-rail input with a wide input common mode voltage range and rail-to-rail output voltage swing.

Furthermore, the SGM8270N-4 provides high slew rate, low noise, low offset current and voltage, and low bias current.

The SGM8270N-4 is available in Green SOIC-14 and TSSOP-14 packages. It is specified over the extended  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$  temperature range.

### FEATURES

- Rail-to-Rail Input and Output
- Wide Input Common Mode and Differential Voltage Ranges
- Low Input Offset Voltage: 1.2mV (MAX)
- Low Input Bias Current
- Low Input Offset Current
- High Input Impedance
- Output Short-Circuit Protection
- Low Noise:  $15\text{nV}/\sqrt{\text{Hz}}$  at 1kHz
- Gain-Bandwidth Product: 2.2MHz
- High Slew Rate: 8V/ $\mu\text{s}$
- $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$  Operating Temperature Range
- Available in Green SOIC-14 and TSSOP-14 Packages

### APPLICATIONS


High Impedance Sensor  
Photodiode Amplifier  
Professional Audio Instrument  
DAC Output Amplifier  
Medical Equipment

## PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM8270N-4	SOIC-14	-40°C to +125°C	SGM8270N-4XS14G/TR	SGM05YXS14 XXXXX	Tape and Reel, 2500
	TSSOP-14	-40°C to +125°C	SGM8270N-4XTS14G/TR	SGM05X XTS14 XXXXX	Tape and Reel, 4000

## MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

## ABSOLUTE MAXIMUM RATINGS

Supply Voltage, $+V_S$ to $-V_S$ .....	40V
Differential Input Voltage, $ V_{ID} $ .....	( $+V_S$ ) - ( $-V_S$ )
Input/Output Voltage Range.....	( $-V_S$ ) - 0.3V to ( $+V_S$ ) + 0.3V
Power Dissipation, $P_D$ @ $T_A = +25^\circ C$	
SOIC-14.....	1.5W
TSSOP-14 .....	1.1W
Package Thermal Resistance	
SOIC-14, $\theta_{JA}$ .....	81°C/W
SOIC-14, $\theta_{JC}$ .....	32°C/W
TSSOP-14, $\theta_{JA}$ .....	108°C/W
TSSOP-14, $\theta_{JC}$ .....	35°C/W
Junction Temperature.....	+150°C
Storage Temperature Range.....	-65°C to +150°C
Lead Temperature (Soldering, 10s).....	+260°C
ESD Susceptibility	
HBM.....	6000V
CDM .....	1000V

## RECOMMENDED OPERATING CONDITIONS

Operating Temperature Range..... -40°C to +125°C

NOTE: 1. It is recommended that CMOS device adopts the proper power supply sequence. Always sort the  $V_S$  first, followed by the inputs and outputs.

## OVERSTRESS CAUTION


Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.

## ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

## DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.







**PIN CONFIGURATIONS**

## ELECTRICAL CHARACTERISTICS

( $V_S = \pm 1.65V$  to  $\pm 18V$  and  $R_L = 2k\Omega$  connected to 0V, Full =  $-40^\circ C$  to  $+125^\circ C$ , typical values are at  $T_A = +25^\circ C$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS
<b>Input Characteristics</b>							
Input Offset Voltage	$V_{OS}$	$V_{CM} = 0V$	+25°C		0.2	1.2	mV
			Full			1.4	
Input Offset Voltage Drift	$\Delta V_{OS}/\Delta T$		Full		0.8		$\mu V/\text{C}$
Input Bias Current	$I_B$	$V_{CM} = 0V$	+25°C		$\pm 5$	$\pm 120$	pA
Input Offset Current	$I_{OS}$	$V_{CM} = 0V$	+25°C		$\pm 5$	$\pm 120$	pA
Maximum Input Difference Bias Current	$I_{IDL}$	$V_S = \pm 18V, V_{ID} = \pm 18V$	+25°C		2	3	$\mu A$
			Full			4	
Input Common Mode Voltage Range	$V_{CM}$		Full	$(-V_S) - 0.1$		$(+V_S) + 0.1$	V
Common Mode Rejection Ratio	CMRR	$V_S = \pm 18V, (-V_S) - 0.1V < V_{CM} < (+V_S) - 1.5V$	+25°C	96	110		dB
			Full	85			
		$V_S = \pm 18V, (-V_S) - 0.1V < V_{CM} < (+V_S) + 0.1V$	+25°C	78	88		
			Full	75			
Open-Loop Voltage Gain	$A_{OL}$	$(-V_S) + 0.2V < V_{OUT} < (+V_S) - 0.2V, R_L = 10k\Omega$	+25°C	101	130		dB
			Full	98			
		$(-V_S) + 0.5V < V_{OUT} < (+V_S) - 0.5V, R_L = 2k\Omega$	+25°C	101	120		
			Full	81			
<b>Output Characteristics</b>							
Output Voltage Swing from Rail	$V_{OUT}$	$V_S = \pm 18V, R_L = 10k\Omega$	+25°C		65	85	mV
			Full			110	
		$V_S = \pm 18V, R_L = 2k\Omega$	+25°C		320	420	
			Full			550	
Output Short-Circuit Current	$I_{SC}$	$V_S = \pm 18V$	+25°C	$\pm 28$	$\pm 40$		mA
<b>Power Supply</b>							
Operating Voltage Range	$V_S$		Full	3.3		36	V
Quiescent Current	$I_Q$	$I_{OUT} = 0A$	+25°C		2	2.6	mA
			Full			3	
Power Supply Rejection Ratio	PSRR	$V_S = 3.3V$ to $36V$	+25°C	105	125		dB
			Full	102			
<b>Dynamic Performance</b>							
Gain-Bandwidth Product	GBP	$C_L = 50pF$	+25°C		2.2		MHz
Phase Margin	$\phi_0$	$C_L = 50pF$	+25°C		65		°
Slew Rate	SR	$V_S = \pm 2.5V$ to $\pm 18V, G = +1$	+25°C		8		V/ $\mu$ s
Overload Recovery Time	ORT	$V_{IN} \times G > V_S$	+25°C		1		$\mu$ s
Total Harmonic Distortion + Noise	THD+N	$V_S = \pm 2.5V$ to $\pm 18V, V_{OUT} = 2V_{P-P}, f = 1kHz, G = +1, R_L = 600\Omega$	+25°C		0.002		%
		$V_S = \pm 2.5V$ to $\pm 18V, V_{OUT} = 2V_{P-P}, f = 1kHz, G = +1, R_L = 2k\Omega$	+25°C		0.0005		
<b>Noise</b>							
Input Voltage Noise		$f = 0.1Hz$ to $10Hz$	+25°C		3.5		$\mu V_{P-P}$
Input Voltage Noise Density	$e_n$	$f = 10Hz$	+25°C		80		$nV/\sqrt{Hz}$
		$f = 1kHz$	+25°C		15		
Input Current Noise Density	$i_n$	$f = 1kHz$	+25°C		300		$fA/\sqrt{Hz}$


## TYPICAL PERFORMANCE CHARACTERISTICS

At  $T_A = +25^\circ\text{C}$ ,  $V_S = 36\text{V}$  and  $R_L = 2\text{k}\Omega$ , unless otherwise noted.


## TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At  $T_A = +25^\circ\text{C}$ ,  $V_S = 36\text{V}$  and  $R_L = 2\text{k}\Omega$ , unless otherwise noted.


Large-Signal Step Response




Small-Signal Step Response




CMRR and PSRR vs. Frequency




Open-Loop Gain and Phase vs. Frequency








Maximum Output Voltage vs. Frequency



EMIRR IN+ vs. Frequency



## TYPICAL PERFORMANCE CHARACTERISTICS (continued)

At  $T_A = +25^\circ\text{C}$ ,  $V_S = 36\text{V}$  and  $R_L = 2\text{k}\Omega$ , unless otherwise noted.

**REVISION HISTORY**



NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

<b>Changes from Original (JANUARY 2023) to REV.A</b>	<b>Page</b>
Changed from product preview to production data.....	All



# PACKAGE INFORMATION

## PACKAGE OUTLINE DIMENSIONS

**SOIC-14**



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
A2	1.25	1.65	0.049	0.065
A3	0.55	0.75	0.022	0.030
b	0.36	0.49	0.014	0.019
D	8.53	8.73	0.336	0.344
E	5.80	6.20	0.228	0.244
E1	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
L	0.45	0.80	0.018	0.032
L1	1.04 REF		0.040 REF	
L2	0.25 BSC		0.01 BSC	
R	0.07		0.003	
R1	0.07		0.003	
h	0.30	0.50	0.012	0.020
θ	0°	8°	0°	8°



NOTES:

1. Body dimensions do not include mode flash or protrusion.
2. This drawing is subject to change without notice.


# PACKAGE INFORMATION

## PACKAGE OUTLINE DIMENSIONS

### TSSOP-14



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	4.860	-	5.100
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		


#### NOTES:

1. This drawing is subject to change without notice.
2. The dimensions do not include mold flashes, protrusions or gate burrs.
3. Reference JEDEC MO-153.


# PACKAGE INFORMATION

## TAPE AND REEL INFORMATION

### REEL DIMENSIONS



### TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

### KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SOIC-14	13"	16.4	6.60	9.30	2.10	4.0	8.0	2.0	16.0	Q1
TSSOP-14	13"	12.4	6.80	5.40	1.50	4.0	8.0	2.0	12.0	Q1

## PACKAGE INFORMATION

### CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

### KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

00002