



SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q , High PSRR, Low Dropout Regulator

GENERAL DESCRIPTION

The SGM2232xQ is a high voltage, ultra-low quiescent current, high PSRR and low dropout voltage linear regulator. It is capable of supplying 150mA output current with typical dropout voltage of 570mV. The operating input voltage range is from 4V to 40V and output voltage range is from 2.5V to 5V.

Other features include under-voltage lockout, short-circuit current limit and thermal shutdown protection. The SGM2232xQ is suitable for various automotive applications.

This device is AEC-Q100 qualified (Automotive Electronics Council (AEC) standard Q100 Grade 1) and it is suitable for automotive applications.

The SGM2232xQ is available in Green SOT-223-3 and SOT-23-5 packages. It operates over an operating temperature range of -40°C to $+125^{\circ}\text{C}$.

APPLICATIONS

Automotive Applications
Industrial Equipment
Medical Equipment
Telecom Equipment
Wireless Equipment

FEATURES

- **AEC-Q100 Qualified for Automotive Applications**
Device Temperature Grade 1
 $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$
- **Operating Input Voltage Range: 4V to 40V**
- **Fixed Output from 2.5V to 5V**
- **150mA Output Current**
- **Output Voltage Accuracy:**
 $\pm 3\%$ at $T_J = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$
- **Low Quiescent Current: 16 μA (TYP)**
- **Low Dropout Voltage:**
570mV (TYP) at 150mA, $V_{OUT} = 5.0\text{V}$
- **High PSRR:**
 - ♦ 84dB (TYP) at 1kHz
 - ♦ 56dB (TYP) at 100kHz
 - ♦ 63dB (TYP) at 1MHz
- **Current Limiting and Thermal Protection**
- **Under-Voltage Lockout (UVLO)**
- **Stable with Low ESR Ceramic Capacitors**
- **-40°C to $+125^{\circ}\text{C}$ Operating Temperature Range**
- **Available in Green SOT-223-3 and SOT-23-5 Packages**

TYPICAL APPLICATION




Figure 1. Typical Application Circuit

SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q, High PSRR, Low Dropout Regulator

PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM2232-2.5Q	SOT-223-3	-40°C to +125°C	SGM2232-2.5QKC3G/TR	0IQ XXXXXX	Tape and Reel, 2500
SGM2232-3.3Q	SOT-223-3	-40°C to +125°C	SGM2232-3.3QKC3G/TR	0MZ XXXXXX	Tape and Reel, 2500
SGM2232-5.0Q	SOT-223-3	-40°C to +125°C	SGM2232-5.0QKC3G/TR	0IP XXXXXX	Tape and Reel, 2500
SGM2232-2.5Q	SOT-23-5	-40°C to +125°C	SGM2232-2.5QN5G/TR	0INXX	Tape and Reel, 3000
SGM2232-3.3Q	SOT-23-5	-40°C to +125°C	SGM2232-3.3QN5G/TR	0IOXX	Tape and Reel, 3000
SGM2232-5.0Q	SOT-23-5	-40°C to +125°C	SGM2232-5.0QN5G/TR	0IMXX	Tape and Reel, 3000

MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code. XX = Date Code.

SOT-223-3

XXXXX

Vendor Code
Trace Code
Date Code - Year

SOT-23-5

YYY X X

Date Code - Week
Date Code - Year
Serial Number

Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS

IN to GND -0.3V to 45V
OUT to GND -0.3V to 7V
Package Thermal Resistance
SOT-223-3, θ_{JA} 57.7°C/W
SOT-223-3, θ_{JB} 10.4°C/W
SOT-223-3, θ_{JC} 32.6°C/W
SOT-23-5, θ_{JA} 164.1°C/W
SOT-23-5, θ_{JB} 28.6°C/W
SOT-23-5, θ_{JC} 51.8°C/W
Junction Temperature +150°C
Storage Temperature Range -65°C to +150°C
Lead Temperature (Soldering, 10s) +260°C
ESD Susceptibility
HBM 3000V
CDM 1000V

RECOMMENDED OPERATING CONDITIONS

Input Voltage Range 4V to 40V
Input Effective Capacitance, C_{IN} 2.2μF (MIN)
Output Effective Capacitance, C_{OUT} 1.5μF to 100μF
Operating Ambient Temperature Range -40°C to +125°C
Operating Junction Temperature Range -40°C to +150°C

OVERSTRESS CAUTION

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.

ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.


DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q, High PSRR, Low Dropout Regulator


PIN CONFIGURATIONS

SGM2232xQ (TOP VIEW)



SOT-223-3

SGM2232xQ (TOP VIEW)



SOT-23-5

PIN DESCRIPTION

PIN		NAME	FUNCTION
SOT-223-3	SOT-23-5		
1	1	IN	Input Supply Voltage Pin. It is recommended to use a 10 μ F or larger ceramic capacitor from IN pin to ground. This ceramic capacitor should be placed as close as possible to the IN pin.
2, TAB	3, 4	GND	Ground.
3	5	OUT	Regulator Output Pin. It is recommended to use a ceramic capacitor with effective capacitance in the range of 1.5 μ F to 100 μ F. This ceramic capacitor should be placed as close as possible to the OUT pin.
—	2	NC	No Connection.

SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q , High PSRR, Low Dropout Regulator

FUNCTIONAL BLOCK DIAGRAM




Figure 2. Block Diagram

SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q, High PSRR, Low Dropout Regulator

ELECTRICAL CHARACTERISTICS

(V_{IN} = V_{OUT(NOM)} + 1.5V, C_{IN} = 10μF, C_{OUT} = 2.2μF, T_J = -40°C to +150°C, typical values are at T_J = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Input Voltage Range	V _{IN}	V _{OUT(NOM)} = 2.5V		4		40	V
		V _{OUT(NOM)} = 3.3V		4		40	
		V _{OUT(NOM)} = 5.0V		5.5		40	
Output Voltage Accuracy	V _{OUT}	V _{IN} = (V _{OUT(NOM)} + 1.5V) to 40V, I _{OUT} = 1mA to 150mA		-3		3	%
Under-Voltage Lockout Thresholds	V _{UVLO}	V _{IN} rising				2.60	V
		V _{IN} falling		1.15			
Line Regulation	ΔV _{LNR}	V _{IN} = (V _{OUT(NOM)} + 1.5V) to 40V, I _{OUT} = 1mA			0.5	10	mV
Load Regulation	ΔV _{LDR}	I _{OUT} = 1mA to 150mA			12	20	mV
Dropout Voltage ⁽¹⁾	V _{DROP}	I _{OUT} = 50mA	V _{OUT(NOM)} = 2.5V		210	450	mV
			V _{OUT(NOM)} = 3.3V		190	420	
			V _{OUT(NOM)} = 5.0V		180	400	
		I _{OUT} = 100mA	V _{OUT(NOM)} = 2.5V		440	850	
			V _{OUT(NOM)} = 3.3V		400	800	
			V _{OUT(NOM)} = 5.0V		365	800	
		I _{OUT} = 150mA	V _{OUT(NOM)} = 2.5V		600	1100	
			V _{OUT(NOM)} = 3.3V		550	1100	
			V _{OUT(NOM)} = 5.0V		570	1100	
Output Current Limit	I _{LIMIT}	V _{OUT} = 90% × V _{OUT(NOM)}		200	350		mA
Short-Circuit Current Limit	I _{SHORT}	V _{OUT} = 0V			285		mA
Quiescent Current	I _Q	I _{OUT} = 0mA			16	35	μA
Start-Up Time	t _{STR}	From V _{IN} rising from 0V to V _{IN} to V _{OUT} = 90% × V _{OUT(NOM)}			200	400	μs
Power Supply Ripple Rejection	PSRR	ΔV _{RIPPLE} = 0.5V _{P-P} , V _{IN} = 14V, I _{OUT} = 10mA	f = 100Hz		95		dB
			f = 1kHz		84		
			f = 100kHz		56		
			f = 1MHz		63		
Thermal Shutdown Temperature	T _{SHDN}				180		°C
Thermal Shutdown Hysteresis	ΔT _{SHDN}				30		°C







NOTE:

1. The dropout voltage is defined as the difference between V_{IN} and V_{OUT} when V_{OUT} falls to 95% × V_{OUT(NOM)}.

SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q , High PSRR, Low Dropout Regulator

TYPICAL PERFORMANCE CHARACTERISTICS







$T_J = +25^\circ\text{C}$, $V_{IN} = 14\text{V}$, $I_{OUT} = 10\text{mA}$, $C_{IN} = 10\mu\text{F}$, $C_{OUT} = 2.2\mu\text{F}$, unless otherwise noted.



SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q , High PSRR, Low Dropout Regulator

TYPICAL PERFORMANCE CHARACTERISTICS (continued)







$T_J = +25^\circ\text{C}$, $V_{IN} = 14\text{V}$, $I_{OUT} = 10\text{mA}$, $C_{IN} = 10\mu\text{F}$, $C_{OUT} = 2.2\mu\text{F}$, unless otherwise noted.



SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q , High PSRR, Low Dropout Regulator

TYPICAL PERFORMANCE CHARACTERISTICS (continued)







$T_J = +25^\circ\text{C}$, $V_{IN} = 14\text{V}$, $I_{OUT} = 10\text{mA}$, $C_{IN} = 10\mu\text{F}$, $C_{OUT} = 2.2\mu\text{F}$, unless otherwise noted.



SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q, High PSRR, Low Dropout Regulator

TYPICAL PERFORMANCE CHARACTERISTICS (continued)



T_J = +25°C, V_{IN} = 14V, I_{OUT} = 10mA, C_{IN} = 10μF, C_{OUT} = 2.2μF, unless otherwise noted.



SGM2232xQ Automotive, 150mA, High Voltage, Ultra-Low I_Q , High PSRR, Low Dropout Regulator

TYPICAL PERFORMANCE CHARACTERISTICS (continued)

$T_J = +25^\circ\text{C}$, $V_{IN} = 14\text{V}$, $I_{OUT} = 10\text{mA}$, $C_{IN} = 10\mu\text{F}$, $C_{OUT} = 2.2\mu\text{F}$, unless otherwise noted.



APPLICATION INFORMATION

The SGM2232xQ is a high voltage, ultra-low quiescent current, high PSRR and low dropout LDO and provides 150mA output current. These features make the device useful in a variety of applications. The SGM2232xQ provides protection functions for output overload, output short-circuit condition and overheating.

Input Capacitor Selection (C_{IN})

The input decoupling capacitor should be placed as close as possible to the IN pin to ensure the device stability. 10μF or larger X7R or X5R ceramic capacitor is selected to get good dynamic performance.

When V_{IN} is required to provide large current instantaneously, a large effective input capacitor is required. Multiple input capacitors can limit the input tracking inductance. Adding more input capacitors is available to restrict the ringing and to keep it below the device absolute maximum ratings. For C_{OUT} with larger capacitance, it is recommended to choose the larger capacitance C_{IN}.

Output Capacitor Selection (C_{OUT})

The output capacitor should be placed as close as possible to the OUT pin. 2.2μF or larger X7R or X5R ceramic capacitor is selected to get good dynamic performance. The minimum effective capacitance of C_{OUT} that makes SGM2232xQ remain stable is 1.5μF. For ceramic capacitor, temperature, DC bias and package size will change the effective capacitance, so enough margin of C_{OUT} must be considered in design. Additionally, C_{OUT} with larger capacitance and lower ESR will help increase the high frequency PSRR and improve the load transient response.

Under-Voltage Lockout (UVLO)

The UVLO circuit monitors the input voltage to prevent the device from turning on before V_{IN} rises above the V_{UVLO} threshold. The UVLO circuit responds quickly to glitches on the IN pin and attempts to disable the output of the device if any of these rails collapses. The local input capacitance prevents severe brownouts in most applications.

Reverse Current Protection

The power transistor has an inherent body diode. This body diode will be forward biased when V_{OUT} > (V_{IN} + 0.3V). When V_{OUT} > (V_{IN} + 0.3V), the reverse current flowing from the OUT pin to the IN pin will damage the SGM2232xQ. If V_{OUT} > (V_{IN} + 0.3V) event would happen in system, one external Schottky diode will be added between OUT pin and IN pin in circuit design to protect the SGM2232xQ.

Output Current Limit and Short-Circuit Protection

When overload events happen, the output current is internally limited to 350mA (TYP). When the OUT pin is shorted to ground, the short-circuit protection will limit the output current to 285mA (TYP).

Thermal Shutdown

When the die temperature exceeds the threshold value of thermal shutdown, the SGM2232xQ will be in shutdown state and it will remain in this state until the die temperature decreases to +150°C.

Power Dissipation (P_D)

Power dissipation (P_D) of the SGM2232xQ can be calculated by the equation $P_D = (V_{IN} - V_{OUT}) \times I_{OUT}$. The maximum allowable power dissipation (P_{D(MAX)}) of the SGM2232xQ is affected by many factors, including the difference between junction temperature and ambient temperature (T_{J(MAX)} - T_A), package thermal resistance from the junction to the ambient environment (θ_{JA}), the rate of ambient airflow and PCB layout. P_{D(MAX)} can be approximated by the following equation:

$$P_{D(MAX)} = (T_{J(MAX)} - T_A) / \theta_{JA} \quad (1)$$

Layout Guidelines

To get good PSRR, low output noise and high transient response performance, the input and output bypass capacitors must be placed as close as possible to the IN pin and OUT pin separately.



REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.



JUNE 2024 – REV.A to REV.A.1	Page
Update Features.....	1
Update Application Information section.....	11
Changes from Original (APRIL 2024) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

SOT-223-3



RECOMMENDED LAND PATTERN (Unit: mm)





Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A		1.800		0.071
A1	0.020	0.100	0.001	0.004
A2	1.500	1.700	0.059	0.067
b	0.660	0.840	0.026	0.033
b1	2.900	3.100	0.114	0.122
c	0.230	0.350	0.009	0.014
D	6.300	6.700	0.248	0.264
E	3.300	3.700	0.130	0.146
E1	6.700	7.300	0.264	0.287
e	2.300 BSC		0.091 BSC	
L	0.750		0.030	
θ	0°	10°	0°	10°

NOTES:



1. Body dimensions do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

PACKAGE OUTLINE DIMENSIONS

SOT-23-5



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.450
A1	0.000	-	0.150
A2	0.900	-	1.300
b	0.300	-	0.500
c	0.080	-	0.220
D	2.750	-	3.050
E	1.450	-	1.750
E1	2.600	-	3.000
e	0.950 BSC		
e1	1.900 BSC		
L	0.300	-	0.600
θ	0°	-	8°
ccc	0.100		


NOTES:

1. This drawing is subject to change without notice.
2. The dimensions do not include mold flashes, protrusions or gate burrs.
3. Reference JEDEC MO-178.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SOT-223-3	13"	12.4	6.55	7.25	1.90	4.0	8.0	2.0	12.0	Q3
SOT-23-5	7"	9.5	3.20	3.20	1.40	4.0	4.0	2.0	8.0	Q3

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18
13"	386	280	370	5

DD0002