

GENERAL DESCRIPTION

The SGM18UB1E1 is an ultra-low capacitance ESD protection device designed to protect circuits from electrostatic discharge.

FEATURES

- **High ESD Withstand Voltage:**
IEC 61000-4-2: $\pm 8\text{kV}$ (Air)
IEC 61000-4-2: $\pm 8\text{kV}$ (Contact)
- **0.35pF (TYP) Channel Input Capacitance**
- **Low Profile Packages: UTDFN-1 $\times$ 0.6-2L and XTDFN-0.6 $\times$ 0.3-2L**
- **Working Voltage: 18V and below**

APPLICATIONS


Cellular Handsets & Accessories
Computers and Peripherals
Audio and Video Equipment
SIM Card Protection
Portable Electronics
10/100Mbit/s Ethernet

PRODUCT SUMMARY

V_{RWM} (MAX)	I_{PP} (MAX)	C_{IN} (TYP)
18V	1.4A	0.35pF


PIN CONFIGURATIONS

(TOP VIEW)



UTDFN-1 $\times$ 0.6-2L

(TOP VIEW)



XTDFN-0.6 $\times$ 0.3-2L

EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Current (t_P : 8/20 μs)	I_{PP}	1.4	A
ESD IEC 61000-4-2 (Air)	V_{ESD}	± 8	kV
ESD IEC 61000-4-2 (Contact)		± 8	
Operating Temperature Range	T_{OP}	-40 to 125	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 to 150	$^{\circ}\text{C}$
Lead Temperature (Soldering, 10s)		+260	$^{\circ}\text{C}$

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM18UB1E1	UTDFN-1×0.6-2L	-40°C to +125°C	SGM18UB1E1XUEG2G/TR	09X	Tape and Reel, 10000
	XTDFN-0.6×0.3-2L	-40°C to +125°C	SGM18UB1E1XXEI2G/TR	07	Tape and Reel, 10000

MARKING INFORMATION

NOTE: X = Date Code.

UTDFN-1×0.6-2L

YY X

— Date Code - Quarter
— Serial Number

NOTE: Fixed character for 07.

XTDFN-0.6×0.3-2L

YY

— Serial Number


Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

ELECTRICAL PARAMETERS

SYMBOL	PARAMETER
V_{RWM}	Reverse Stand-Off Voltage
V_{BR}	Reverse Breakdown Voltage
I_R	Reverse Leakage Current
$I_{R@BR}$	Reverse Leakage Current @ Breakdown
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
R_{DYN}	Dynamic Resistance



ELECTRICAL CHARACTERISTICS

(T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Reverse Stand-Off Voltage	V _{RWM}				18	V
Reverse Breakdown Voltage	V _{BR}	I _R = 1mA	19	21	25	V
Reverse Leakage Current	I _R	V _R = 18V		20	100	nA
Channel Input Capacitance	C _{IN}	V _R = 0V, f = 1MHz, I/O to GND		0.35		pF
ESD Clamping Voltage ⁽²⁾	V _C	I _{TLP} = 8A (Equivalent IEC61000-4-2 Contact +4kV)		31		V
		I _{TLP} = 16A (Equivalent IEC61000-4-2 Contact +8kV)		36		V
Dynamic Resistance ⁽²⁾	R _{DYN}	t _p = 100ns		0.62		Ω

NOTES:

1. Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC 61000-4-5, 2Ω source impedance.
2. Non-repetitive current pulse. Transmission Line Pulse (TLP) t_p = 100ns, square pulse.

Positive 8kV:




Figure 1. Typical Pulses ESD 8kV Contact per IEC 61000-4-2

Negative 8kV:






Figure 2. Typical Pulses ESD -8kV Contact per IEC 61000-4-2

TYPICAL PERFORMANCE CHARACTERISTICS


ESD pulse waveform per IEC61000-4-2






8/20μs waveform per IEC61000-4-5





TLP_Pin1(+) to Pin2(-)



TLP_Pin1(-) to Pin2(+)


Positive Clamp Voltage vs. Peak Pulse Current ($t_P = 8/20\mu s$)Negative Clamp Voltage vs. Peak Pulse Current ($t_P = 8/20\mu s$)

TYPICAL PERFORMANCE CHARACTERISTICS (continued)



APPLICATION INFORMATION

The SGM18UB1E1 is designed to provide a bidirectional line for dissipating ESD events on high-speed signal. And it is suitable for lines with positive and negative signal polarity relative to the ground.



The following guidelines are recommended:

1. TVS Placement

Place the SGM18UB1E1 as close to the input connector as possible.

2. TVS's Trace Layout

Avoid running protected traces in parallel with unprotected traces.

Minimize the path length between the SGM18UB1E1 and the protected line.

Minimize parallel signal path length.

Route the protected traces as straight as possible.

3. GND Layout

Avoid using a common ground point shared with the SGM18UB1E1 transient return path.

Minimize the length of the SGM18UB1E1 transient return path to ground.

Use ground vias as close as possible to the SGM18UB1E1 transient return to ground.

REVISION HISTORY


NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Original (MAY 2025) to REV.A	Page
Changed from product preview to production data.....	All


PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS


UTDFN-1×0.6-2L




TOP VIEW



BOTTOM VIEW



SIDE VIEW



RECOMMENDED LAND PATTERN (Unit: mm)


Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.450	0.500	0.550
A1	0.000	-	0.050
A2	0.120	0.150	0.180
b	0.200	0.250	0.300
D	0.950	1.000	1.050
E	0.550	0.600	0.650
e	0.650 BSC		
L	0.450	0.500	0.550
L1	0.050 REF		

NOTE: This drawing is subject to change without notice.


PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS


XTDFN-0.6×0.3-2L




TOP VIEW



BOTTOM VIEW



SIDE VIEW



RECOMMENDED LAND PATTERN (Unit: mm)


Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.280	0.300	0.320
A1	0.000	0.020	0.050
A2	0.050	0.100	0.150
b1	0.130	0.180	0.230
b2	0.140	0.190	0.240
D	0.550	0.600	0.650
E	0.250	0.300	0.350
e	0.350 BSC		
L	0.200	0.250	0.300
L1	0.030 BSC		
L2	0.025 BSC		
L3	0.035 BSC		

NOTE: This drawing is subject to change without notice.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
UTDFN-1×0.6-2L	7"	8.6	0.70	1.15	0.57	4.0	2.0	2.0	8.0	Q1
XTDFN-0.6×0.3-2L	7"	8.6	0.37	0.67	0.34	4.0	2.0	2.0	8.0	Q1

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

DD0002