

GENERAL DESCRIPTION

The 74AHCT244 is an octal buffer/line driver with non-inverting 3-state outputs, and it is designed for 4.5V to 5.5V V_{CC} operation.

The device can be used as two 4-bit buffers or one 8-bit buffer. The $\overline{1OE}$ and $\overline{2OE}$ are two output enable inputs, and each controls four of the 3-state outputs. When $\overline{nOE}$ is set high, the outputs are in high-impedance state. When $\overline{nOE}$ is set low, data transmits from the nAn inputs to the nYn outputs.

FUNCTION TABLE


CONTROL INPUT	INPUT	OUTPUT
$\overline{nOE}$	nAn	nYn
L	L	L
L	H	H
H	X	Z

H = High Voltage Level
L = Low Voltage Level
Z = High-Impedance State
X = Don't Care

FEATURES

- Supply Voltage Range: 4.5V to 5.5V
- Input Accept Voltages Higher than the Supply Voltage
- +8mA/-8mA Output Current
- 3-State Buffers
- -40°C to +125°C Operating Temperature Range
- Available in Green SOIC-20 and TSSOP-20 Packages

LOGIC DIAGRAM




PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
74AHCT244	SOIC-20	-40°C to +125°C	74AHCT244XS20G/TR	74AHCT244XS20 XXXXXX	Tape and Reel, 1500
	TSSOP-20	-40°C to +125°C	74AHCT244XTS20G/TR	0KGXTS20 XXXXXX	Tape and Reel, 4000

MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

XXXXX



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

Supply Voltage Range, V_{CC}	-0.5V to 7.0V
Input Voltage Range, V_I ⁽²⁾	-0.5V to 7.0V
Output Voltage Range, V_O ⁽²⁾	-0.5V to MIN(7.0V, $V_{CC} + 0.5V$)
Input Clamp Current, I_{IK} ($V_I < 0V$)	-20mA
Output Clamp Current, I_{OK} ($V_O > V_{CC}$ or $V_O < 0V$)	$\pm 20mA$
Continuous Output Current, I_O	$\pm 25mA$
Continuous Current through V_{CC} or GND	$\pm 75mA$
Junction Temperature ⁽³⁾	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s)	+260°C
ESD Susceptibility	
HBM	4000V
CDM	1000V

RECOMMENDED OPERATING CONDITIONS

Function Supply Voltage Range, V_{CC}	4.5V to 5.5V
Input Voltage Range, V_I	0V to 5.5V
Output Voltage Range, V_O	0V to V_{CC}
Output Current, I_O	$\pm 8mA$
Input Transition Rise or Fall Rate, $\Delta t/\Delta V$	
$V_{CC} = 4.5V$ to 5.5V	10ns/V (MAX)
Operating Temperature Range	-40°C to +125°C

OVERSTRESS CAUTION

1. Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.
2. The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.
3. The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.


ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATIONS



PIN DESCRIPTION

PINS	NAME	FUNCTION
1, 19	$\overline{1OE}$, $\overline{2OE}$	Output Enable Inputs (Active Low).
2, 4, 6, 8	1A0, 1A1, 1A2, 1A3	Data Inputs.
18, 16, 14, 12	1Y0, 1Y1, 1Y2, 1Y3	Data Outputs.
10	GND	Ground.
11, 13, 15, 17	2A0, 2A1, 2A2, 2A3	Data Inputs.
9, 7, 5, 3	2Y0, 2Y1, 2Y2, 2Y3	Data Outputs.
20	V_{CC}	Supply Voltage.

ELECTRICAL CHARACTERISTICS(Full = -40°C to +125°C, all typical values are measured at T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS
High-Level Input Voltage	V _{IH}	V _{CC} = 4.5V to 5.5V	Full	2			V
Low-Level Input Voltage	V _{IL}	V _{CC} = 4.5V to 5.5V	Full			0.8	V
High-Level Output Voltage	V _{OH}	V _{CC} = 4.5V, I _{OH} = -50μA	Full	4.45	4.495		V
		V _{CC} = 4.5V, I _{OH} = -8mA	Full	4	4.25		
Low-Level Output Voltage	V _{OL}	V _{CC} = 4.5V, I _{OL} = 50μA	Full		0.005	0.05	V
		V _{CC} = 4.5V, I _{OL} = 8mA	Full		0.25	0.5	
Off-State Output Current	I _{OZ}	V _{CC} = 5.5V, V _O = V _{CC} or GND	Full		±0.02	±2	μA
Input Leakage Current	I _I	V _{CC} = 0V to 5.5V, V _I = 5.5V or GND	Full		±0.02	±2	μA
Supply Current	I _{CC}	V _{CC} = 5.5V, V _I = V _{CC} or GND, I _O = 0A	Full		0.02	2	μA
Additional Supply Current	ΔI _{CC}	Per input pin at 3.4V, other pins at V _{CC} or GND, V _{CC} = 5.5V	Full		0.05	0.5	mA
Input Capacitance	C _I	V _{CC} = 5V, V _I = V _{CC} or GND	+25°C		7		pF
Output Capacitance	C _O	V _{CC} = 5V, V _O = V _{CC} or GND	+25°C		5		pF

DYNAMIC CHARACTERISTICS(See Figure 1 for test circuit. Full = -40°C to +125°C, all typical values are measured at V_{CC} = 5V ± 0.5V and T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN ⁽¹⁾	TYP	MAX ⁽¹⁾	UNITS
Propagation Delay	t _{PLH}	nAn to nYn	C _L = 15pF	Full	0.5	3.5	ns
			C _L = 50pF	Full	1	4.5	
	t _{PHL}	nAn to nYn	C _L = 15pF	Full	1	5	
			C _L = 50pF	Full	1	5.5	
Enable Time	t _{PZH}	n $\overline{\text{OE}}$ to nYn	C _L = 15pF	Full	1	6	ns
			C _L = 50pF	Full	1	7	
	t _{PZL}	n $\overline{\text{OE}}$ to nYn	C _L = 15pF	Full	1	5.5	
			C _L = 50pF	Full	1	6.5	
Disable Time	t _{PHZ}	n $\overline{\text{OE}}$ to nYn	C _L = 15pF	Full	0.5	5	ns
			C _L = 50pF	Full	0.5	8	
	t _{PLZ}	n $\overline{\text{OE}}$ to nYn	C _L = 15pF	Full	0.5	4	
			C _L = 50pF	Full	0.5	7	
Power Dissipation Capacitance ⁽²⁾	C _{PD}	No load, f = 1MHz	+25°C		13		pF

NOTES:

- Specified by design and characterization, not production tested.
- C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$$


where:

f_i = Input frequency in MHz.f_o = Output frequency in MHz.C_L = Output load capacitance in pF.V_{CC} = Supply voltage in Volts.

N = Number of inputs switching.

 $\Sigma(C_L \times V_{CC}^2 \times f_o)$ = Sum of the outputs.

TEST CIRCUIT



Test conditions are given in Table 1.

Definitions for test circuit:

R_L : Load resistance.

C_L : Load capacitance (includes jig and probe).

R_T : Termination resistance (equals to output impedance Z_O of the pulse generator).


V_{EXT} : External voltage is used to measure switching time.

Figure 1. Test Circuit for Measuring Switching Times

Table 1. Test Conditions

SUPPLY VOLTAGE	INPUT		LOAD		V_{EXT}		
V_{CC}	V_I	t_R, t_F	C_L	R_L	t_{PLH}, t_{PHL}	t_{PLZ}, t_{PZL}	t_{PHZ}, t_{PZH}
4.5V to 5.5V	V_{CC}	$\leq 3.0\text{ns}$	15pF, 50pF	1k Ω	Open	V_{CC}	GND

WAVEFORMS




Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 2. Input (nAn) to Output (nYn) Propagation Delays



Test conditions are given in Table 1.

Measurement points are given in Table 2.

Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 3. Enable and Disable Times

Table 2. Measurement Points

SUPPLY VOLTAGE	INPUT		OUTPUT		
V_{CC}	V_I	$V_M^{(1)}$	V_M	V_X	V_Y
4.5V to 5.5V	V_{CC}	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$

NOTE:

1. The measurement points should be V_{IH} or V_{IL} when the input rising or falling time exceeds 3.0ns.


REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

OCTOBER 2023 – REV.A to REV.A.1	Page
Updated GENERAL DESCRIPTION section.....	1
Updated ABSOLUTE MAXIMUM RATINGS and RECOMMENDED OPERATING CONDITIONS sections.....	2
Added TSSOP-20 package.....	All
Changes from Original (OCTOBER 2022) to REV.A	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

SOIC-20





Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	2.350	2.650	0.093	0.104
A1	0.100	0.300	0.004	0.012
A2	2.100	2.500	0.083	0.098
b	0.330	0.510	0.013	0.020
c	0.204	0.330	0.008	0.013
D	12.520	13.000	0.493	0.512
E	7.400	7.600	0.291	0.299
E1	10.210	10.610	0.402	0.418
e	1.27 BSC		0.050 BSC	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

NOTES:


1. Body dimensions do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

PACKAGE OUTLINE DIMENSIONS

TSSOP-20



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	6.400	-	6.600
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		


NOTES:

1. Body dimensions do not include mold flash or protrusion.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-153.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SOIC-20	13"	24.4	10.90	13.30	3.00	4.0	12.0	2.0	24.0	Q1
TSSOP-20	13"	16.4	6.80	6.90	1.50	4.0	8.0	2.0	16.0	Q1

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002